

## COUNTERBLOW HAMMER BECHE (SCHLOEMANN) DGH 40

### TECHNICAL DATA

|                                          |             |
|------------------------------------------|-------------|
| ENERGY OF BLOW                           | 40 000 Kg/m |
| RAM STROKE                               | 1450 mm     |
| MAX. STROKING RATE                       | 80 s.p.m    |
| AVERAGE STROKING RATE                    | 6 s.p.m     |
| UPPER RAM WEIGHT                         | 43T         |
| LOWER RAM WEIGHT                         | 47T         |
| AIR CONSUMPTION (hardest stroke)         |             |
| Cold air                                 | 5,3 m3      |
| Hot air 220°C                            | 3,2 m3      |
| AIR CONSUMPTION                          |             |
| Cold air (at average stroking rate)      | 32 m3/mn    |
| Hot air 220°C (at average stroking rate) | 19 m3/mn    |
| USABLE COMPRESSOR POWER                  |             |
| Cold air (at average stroking rate)      | 240 HP      |
| Hot air 220°C (at average stroking rate) | 140 HP      |
| DISTANCE BETWEEN SLIDES                  | 1200 mm     |
| MIN. DIES HEIGHT (witout dovetail)       | 575 mm      |
| HEIGHT ABOVE THE FLOOR                   | 6200 mm     |
| TOTAL WEIGHT                             | 235T        |

